

# PATENT ABSTRACTS OF JAPAN

(11)Publication number : 2003-206826

(43)Date of publication of application : 25.07.2003

(51)Int.Cl.

F02M 61/16

F02M 51/06

F02M 51/08

F02M 61/18

(21)Application number : 2002-238133

(71)Applicant : DENSO CORP

(22)Date of filing : 19.08.2002

(72)Inventor : IWANO AKIRA

HOKAO TAKAYUKI

(30)Priority

Priority number : 2001340629

Priority date : 06.11.2001


Priority country : JP

## (54) FUEL INJECTION VALVE

(57)Abstract:

**PROBLEM TO BE SOLVED:** To provide a fuel injection valve having a structure that improves atomization of fuel spray and valve tightness and facilitates assembling by press fitting.

**SOLUTION:** The fuel injection valve comprises a nozzle hole plate 28 that is formed in a cup shape and is entirely circumferentially coupled to a valve body 29, and has a bottom 28b having a nozzle hole 28a and a cylinder part 28h that is stood from the peripheral edge of the bottom 28b and is forced into the side wall part 29hh of the valve body 29. The fuel injection valve also comprises a resin made sleeve 50 having a resin annular part 50b having an opening 50a opening toward the downstream side of the fuel injection of the nozzle hole plate 28 and a resin cylindrical part 50h that is stood from the peripheral edge of the resin annular part 50b and forced into the side wall part 29hh. A projection 28p projects from



the nozzle hole plate 28, a notch 50p corresponding to the projection 28p is disposed in the sleeve 50, and they engage with each other.

---

## LEGAL STATUS

[Date of request for examination] 06.10.2004

[Date of sending the examiner's decision of rejection]

[Kind of final disposal of application other than the examiner's decision of rejection or application converted registration]

[Date of final disposal for application]

[Patent number]

[Date of registration]

[Number of appeal against examiner's decision of rejection]

[Date of requesting appeal against examiner's decision of rejection]

[Date of extinction of right]

Copyright (C); 1998,2003 Japan Patent Office